



- LED display of Speed & Time
- Digital control of parameters
- Automatic soft start
- Ten Acceleration & Deceleration rates
- Ten Memory / Preset Program
- 1-90 second Pulse (Quick spin)
- CE Marked (see safety features)
- Sensors Tacho, Imbalance & Lid
- Stainless steel bowl & barrier ring




Speed 1000-3800 Rpm Max Rcf 2500G Timer 0-60mins Size 29x40x48Cm Weight 26.5Kg


2040 Rotors

Adaptors for 5556 (set of 4) Capacity below per bucket

Part Nos	5419	5421	5422	5423	5424	5425
Description	Sealed lids	100ml	50ml	4-7ml vacut	5ml	5/6ml
Nos/bucket	1	1	1	7	12	9
Tube size	n/a	45x100mm	33x105mm	11.5x100mm	13x100mm	14x100mm

Part Nos	5426	5427	5428	5429	541F	5422U
Description	10ml	12ml	15ml	20ml	15ml Falcon	27ml Universal
Nos/bucket	5	3	7	3	2	1
Tube size	16.5x108mm	17.5 x 100mm	17x100mm	33x105mm	17x120mm	13x100mm

 **5556**
Swing out rotor including buckets
4 x 250ml bottle max
Max Speed 3800Rpm Rcf 2500G

 **Bucket**
shown with 5419 Sealed lid

