

Arc Premier 2489 UV/Visible Detector

Whether you are doing routine UV-based applications or pushing the limits of detection with low-level impurity analyses, the Waters™ Arc™ Premier 2489 UV/Visible (UV/Vis) Detector is the best detection choice for performance, reliability, usability, incorporating MaxPeak™ High Performance Surfaces (HPS) technology. The Arc Premier 2489 UV/Vis Detector is the most sensitive and versatile dual-wavelength absorbance detector available for HPLC. The design combines a high energy deuterium source, a precise optical design, and low noise, high speed electronics. These advanced capabilities take UV/Vis detection performance to a new level.

OPERATING SPECIFICATIONS¹

Wavelength range	190 to 700 nm
Bandwidth	≤5 nm
Wavelength accuracy	±1 nm (via patented ² Erbium filter)
Wavelength repeatability	±0.1 nm
Linearity ³	≤5% at 2.5 AU, propylparaben, 257 nm, analytical flow cell
Baseline noise, ³ single wavelength	≤5 x 10 ⁻⁶ AU peak to peak, 230 nm, 10 points/s, 1.0 s, 30-s segments, dry analytical flow cell
Baseline noise, ³ dual wavelength	≤35 x 10 ⁻⁶ AU peak to peak, 230 nm, 280 nm, 1 point/s, 2.0 s, 30-s segments, dry analytical flow cell
Drift ³	≤1 x 10 ⁻⁴ AU/hour, 239 nm, 2 points/s, 1.0 s, 30-s segments, dry analytical flow cell
Measurement range	0.0001 to 4.0000 AU
Sampling rate	Up to 80 points/s

OPTICAL COMPONENT SPECIFICATIONS

Light source	Deuterium arc lamp
Warranty:	2000 hours or one year (whichever comes first)
Flow cell design	Patented TaperSlit™ ⁴
Path length	10 mm (analytical cell)
Cell volume	16.3 µL (analytical cell)
Pressure limit	1000 psi (analytical cell)
Wetted materials	Fluoropolymer, fused silica, MP35N, PEEK, titanium



ELECTRICAL SPECIFICATIONS

Power requirements	100 to 240 VAC
Line frequency	50 to 60 Hz
Power consumption	195 VA (nominal)
Inputs	Four event inputs
Outputs	Four outputs (2 analog, 2 event)

PHYSICAL/ENVIRONMENTAL SPECIFICATIONS

Dimensions	Width: 34.3 cm (13.5 inches) Height: 20.8 cm (8.2 inches) Depth: 61.0 cm (24.0 inches) Weight: 13.8 kg (30.5 pounds)
Operating temperature range	4 to 40 °C (39.2 to 104 °F)
Operating humidity range	20% to 80%, non-condensing
Audible noise	<58 dBA

ORDERING INFORMATION

PART NUMBER

Arc Premier 2489 UV/Visible Detector (MaxPeak HPS analytical flow cell included)	176019009
Analytical* (biocompatible)	205002277

* Compatible with ACQUITY™ Arc Systems only.

References

1. All performance specifications are measured following a warm-up period of one hour with ambient $\Delta T \leq \pm 2.0$ °C/hour.
2. U.S. Patent Numbers: 6,423,249 and 6,783,705.
3. ASTM E685-93.
4. U.S. Patent Number: US 5,883,721.

Waters

THE SCIENCE OF WHAT'S POSSIBLE.™

Waters, The Science of What's Possible, ACQUITY, TaperSlit, MaxPeak, and Arc are trademarks of Waters Corporation. All other trademarks are the property of their respective owners.

Waters Corporation
34 Maple Street
Milford, MA 01757 U.S.A.
T: 1 508 478 2000
F: 1 508 872 1990
waters.com